

DATA LOGGER V1000+



- Built-in Web Server, supporting LAN monitoring
- 12 Months data storage
- Automatic network-clock synchronization
- RS485 Interface for the Connection of Inverters
- Standard RJ45 Path Cable
- Supports export control

Model	V1000+
Connection	Inverter: RS485 Router: RJ45
Access Number	40pcs
Transmission maximum distance	1200m
Display	LED
Input	
Input Voltage	Input: AC 90V-250V 50/60Hz Output: DC 5V
Static Current Consumption	1A
General	
Operating temperature	-25°C~55°C
Humidity	10%~95% relative humidity, no condensation
IP Rating	IP20
Dimension (L*W*H)	118mm*78mm*29mm
Certification	
Safety	FCC, CE, ROHS

WIFI Communication Module PV WIFI-R



- Plug and play, quick and convenient
- Preferred monitoring solution for residential us

Model	PV WIFI-R
Connection	TTL
Standards	802.11 b/g/n
Transmission maximum distance	100m Unobstructed environment
Setting	APP/WEB
Input	
Input Voltage	DC 5V
Static Power Consumption	<1.6W
General	
Operating temperature	-25°C~60°C
Humidity	0%~100% relative humidity, no condensation
IP Rating	IP65
Dimension (L*W*H)	71.4mm*71mm*38mm
Certification	
Safety	FCC, CE, ROHS

GPRS Communication Module PV GPRS-R



- Plug and play, quick and convenient
- Mobile internet monitoring, best suited for rural and remote areas

Model	PV GPRS-R
Connection	TTL
Standards	GSM/GPRS
Transmission maximum distance	---
Setting	Plug and Play
Input	
Input Voltage	DC 5V
Static Power Consumption	<2W
General	
Operating temperature	-25°C~60°C
Humidity	0%~100% relative humidity, no condensation
IP Rating	IP65
Dimension (L*W*H)	71.4mm*71mm*38mm
Certification	
Safety	FCC, CE, ROHS

4G Communication Module PV 4G-R



- Plug and play, quick and convenient
- Mobile internet monitoring, best suited for rural and remote areas

Model	PV 4G-R
Connection	TTL
Standards	FDD/TDD - LTE
Transmission maximum distance	---
Setting	Plug and Play
Input	
Input Voltage	DC 5V
Static Power Consumption	<3.5W
General	
Operating temperature	-25°C~60°C
Humidity	0%~90% relative humidity, no condensation
IP Rating	IP65
Dimension (L*W*H)	122.8mm*79mm*34mm
Certification	
Safety	FCC, CE, ROHS