

SINGLE PHASE & DUAL MPPT

SE 4/5/6KTL-D1/G2

Application: Family Use



SUPERIOR EFFICIENCY

- Maximum efficiency 98.2%
- String current 13A, compatible with high power modules
- 150% PV configuration, 110% output overload



HIGH RELIABILITY

- IP65 waterproof and dustproof, C5 anti-corrosion
- Compatible with wide power grid voltage and high harmonic power grid environment
- DC /AC SPD optional, AFCI detection optional



INTELLIGENT MAINTENANCE

- Remote configuration and upgrade
- Supports export power control

Model	SE 4KTL-D1/G2	SE 5KTL-D1/G2	SE 6KTL-D1/G2
Efficiency			
Max. Efficiency			
European Efficiency	98.0%	98.2%	98.2%
97.0%	97.3%	97.4%	97.4%
Input(PV)			
Max. Input Voltage		550V	
Max. PV configuration (STC)		150%	
Rated Input Voltage		360V	
Max. Input Current		26A (2*13A)	
Max. Short Circuit Current		30A (2*15A)	
Start Input Voltage		90V	
MPPT Operating Voltage Range		70V-540V	
Max. Number of PV Strings		2(1/1)	
No. of MPPTs		2	
Output(Grid)			
Rated AC Active Power	4,000W	5,000W	6,000W
Max. AC Apparent Power	4,400VA	5,500VA	6,000VA
Max. AC Active Power (PF=1)	4,400W	5,500W	6,000W
Max. AC Output Current	20A	25A	27.3A
Rated AC Voltage	220V/230V, L+N+PE		
AC Voltage Range①	160V-300V (Adjustable)		
Rated Grid Frequency	50Hz / 60Hz		
Grid Frequency Range②	45Hz-55Hz / 55Hz-65Hz (Adjustable)		
THDI	<3% (Rated Power)		
DC Current Injection	<0.5%In		
Power Factor	>0.99 Rated power (Adjustable 0.8 Leading-0.8 Lagging)		
Protection			
DC switch		Support	
Anti-islanding protection		Support	
AC overcurrent protection		Support	
AC short circuit protection		Support	
DC reverse connection		Support	
Surge Arrester		DC Type III (Optional) / AC Type III	
Insulation detection		Support	
Leakage current protection		Support	
General			
Topology		Transformerless	
IP Rating		IP65	
Night Self Consumption		<1W	
Cooling		Natural cooling	
Operating Temperature Range		-25°C-60°C	
Relative Humidity Range		0-100%	
Max. Operating Altitude		4000m	
Noise (typical)		30dB	
Dimensions (W*H*D)		347mm*350mm*137mm	
Weight		8.5Kg	
HMI & COM			
Display	Wireless & APP+LED, LCD (Optional)		
Communication	WiFi (Optional) / GPRS (Optional) / RS485 (Optional)		
Certification			
Safety	IEC62109-1, IEC62109-2		
Grid Code	IEC61727 / 62116, ABNT 16149 / 16150, IEEE 1547, AS 4777		
Warranty			
	5 Years		

Remarks: • ①②The range of output voltage and frequency may vary depending upon different grid codes.
• Specifications are subject to change without advance notice.