

THREE PHASE & DUAL MPPT

SE 5/6/8/10/12/15KTL-D3/G2

Application: Small-sized Industrial and Residential Use



SUPERIOR EFFICIENCY

- Maximum efficiency 98.3%
- Max String Current 20A, compatible with 600W+ modules
- 150% PV configuration, 110% output overload



HIGH RELIABILITY

- Die-cast aluminum case, IP66 waterproof and dustproof, C5 anti-corrosion
- DC /AC SPD, AFCI detection optional
- Compatible with wide power grid voltage and high harmonic power grid environment



INTELLIGENT MAINTENANCE

- App quick commissioning
- Remote configuration and upgrade
- Supports export control

Model	SE 5KTL-D3/G2	SE 6KTL-D3/G2	SE 8KTL-D3/G2	SE 10KTL-D3/G2	SE 12KTL-D3/G2	SE 15KTL-D3/G2
Efficiency						
Max. Efficiency	98.2%	98.2%	98.2%	98.2%	98.3%	98.3%
European Efficiency	97.8%	97.8%	97.8%	97.8%	97.8%	97.8%
Input (PV)						
Max. Input Voltage	1100V					
Max. PV configuration	150%					
Rated Input Voltage	620V					
Max. Input Current	2*15A			2*15A+15A		
Max.Short Circuit Current	2*20A			2*20A+20A		
Start Input Voltage	180V					
MPPT Operating Voltage Range	160V-1000V					
Max. Number of PV Strings	2 (1/1)			3 (2/1)		
No. of MPPTs	2					
Output (Grid)						
Rated AC Active Power	5000W	6,000W	8,000W	10,000W	12,000W	15,000W
Max. AC Apparent Power	5500VA	6,600VA	8,800VA	11,000VA	13,200VA	16,500VA
Max. AC Active Power (PF=1)	5500W	6,600W	8,800W	11,000W	13,200W	16,500W
Max. AC Output Current	3*8.4A	3*10.1A	3*13.4A	3*16.8A	3*20.2A	3*25.3A
Rated AC Voltage	380V / 400V / 415V, 3W+N+PE					
AC Voltage Range ^①	260V-510V (Adjustable)					
Rated Grid Frequency	50Hz / 60Hz					
Grid Frequency Range ^②	45Hz-55Hz / 55Hz-65Hz (Adjustable)					
THDI	<3%@Rated Power					
DC Current Injection	<0.5%@Rated Current					
Power Factor	> 0.99 Rated power (Adjustable 0.8 LD - 0.8 LG)					
Protection						
DC switch	Support					
Anti-islanding protection	Support					
AC overcurrent protection	Support					
AC short circuit protection	Support					
DC reverse connection	Support					
Surge Arrester	AC Type III (Type II optional) / DC Type III (Type II optional)					
Insulation detection	Support					
String current detection	Support					
Leakage current protection	Support					
General						
Topology	Transformerless					
IP Rating	IP66					
Night Self Consumption	<1W					
Cooling	Natural cooling					
Operating Temperature Range	-25°C-60°C					
Relative Humidity Range	0-100%					
Max. Operating Altitude	4000m					
Noise	<30dB					
Dimensions (W*H*D)	398mm*460mm*190mm					
Weight	23Kg					
HMI & COM						
Display	Wireless & APP +LED, LCD (Optional)					
Communication	RS485, Optional: WiFi / GPRS / 4G / LAN					
Certification						
Safety	IEC62109-1, IEC62109-2					
Grid Code	VDE-AR-N 4105, EN 50549-1, CEI 0-21, UNE 206006/206007-1, RD 1699/661&413, IEC 61727/62116, AS4777.2					
Warranty	5 Years					

Remarks : • ^{①②}The range of output voltage and frequency may vary depending upon different grid codes.
• Specifications are subject to change without advance notice.