



Product Service

Attestation of Conformity

No. N8A 001965 0021 Rev. 02

Holder of Certificate: **Shenzhen Senergy Technology Co., Ltd.**Room 405, Building A
Co-talent Creative Park
No.2, LiuXian Road, Block 68, Xin'an Street
Bao'an District
518101 Shenzhen
PEOPLE'S REPUBLIC OF CHINA**Product:** **Converter
(Grid-Tied Solar Inverter)**

This Attestation of Conformity is issued on a voluntary basis according to the Low Voltage Directive 2014/35/EU relating to electrical equipment designed for use within certain voltage limits. It confirms that the listed equipment complies with the principal protection requirements of the directive and is based on the technical specifications applicable at the time of issuance. It refers only to the particular sample submitted for testing and certification. For details see: www.tuvsud.com/ps-cert

Test report no.: 64290203091103**Date,** 2022-09-08

(Billy Qiu)

Page 1 of 5

After preparation of the necessary technical documentation as well as the EU declaration of conformity the required CE marking can be affixed on the product. The declaration of conformity is issued under the sole responsibility of the manufacturer. Other relevant EU-directives have to be observed.



Attestation of Conformity

No. N8A 001965 0021 Rev. 02

Model(s): SE 2KTL-S1/G2, SE 3KTL-S1/G2, SE 3.6KTL-S1/G2, SE 4KTL-D1/G2, SE 5KTL-D1/G2, SE 6KTL-D1/G2, SE 1.5KTL-S1/G2P, SE 2KTL-S1/G2P, SE 3KTL-S1/G2P, SE 3.6KTL-S1/G2P, SE 3.68KTL-D1/G2P, SE 4KTL-D1/G2P, SE 4.6KTL-D1/G2P, SE 5KTL-D1/G2P, SE 6KTL-D1/G2P, VP 2KTL-S1/G2P, VP 3KTL-S1/G2P, VP 3.6KTL-S1/G2P

Parameters:

Model	SE 2KTL-S1/G2	SE 3KTL-S1/G2	SE 3.6KTL-S1/G2	SE 4KTL-D1/G2	SE 5KTL-D1/G2	SE 6KTL-D1/G2
PV terminal						
Vmax. PV	500Vd.c.			550Vd.c.		
MPPT Voltage Range	50-490Vd.c.			70-540Vd.c.		
MPPT Tracker number	1			2		
Max. continuous PV input current per tracker	13Ad.c.			13/13Ad.c.		
Isc PV per tracker	15Ad.c.			15/15Ad.c.		
Grid terminal						
Rated voltage	220/230/240 Va.c.					
Rated frequency	50/60 Hz					
Maximum continuous output current	10Aa.c.	15Aa.c.	16Aa.c.	20Aa.c.	25Aa.c.	27.3Aa.c.
Rated output current	9.1/8.7/ 8.3 Aa.c.	13.6/13.0/ 12.5 Aa.c.	16/15.7/ 15.0 Aa.c.	18.2/17.4/ 16.7 Aa.c.	22.7/21.7/ 20.8 Aa.c.	27.3/26.1/ 25.0 Aa.c.
Maximum output current	10.0/9.6/ 9.2 Aa.c.	15.0/14.3/ 13.8 Aa.c.	16/15.7/ 15.0 Aa.c.	20.0/19.1/ 18.3 Aa.c.	25.0/23.9/ 22.9 Aa.c.	27.3/26.1/ 25.0 Aa.c.
Rated output power	2000W	3000W	3600W	4000W	5000W	6000W
Rated output Apparent power	2000VA	3000VA	3600VA	4000VA	5000VA	6000VA
Maximum continuous output Apparent power	2200VA	3300VA	3600VA	4400VA	5500VA	6000VA
Power factor (Cos phi), adjustable	0.8 leading ~ 0.8 lagging					
Enclosure	IP65					
Temperature Range	-25°C ~ +60°C (derating at 45°C)					
Protective Class	I					
Altitude	up to 4000 m					



Attestation of Conformity

No. N8A 001965 0021 Rev. 02

Model	SE 1.5KTL-S1/G2P	SE 2KTL-S1/G2P	SE 3KTL-S1/G2P	SE 3.6KTL-S1/G2P
PV terminal				
Vmax. PV	500Vd.c.			
MPPT Voltage Range	50-490Vd.c.			
MPPT Voltage Range (full load)	100 ~ 430Vd.c.	140 ~ 430Vd.c.	210 ~ 430Vd.c.	250 ~ 430Vd.c.
MPPT Tracker number	1			
Max. continuous PV input current per tracker	15Ad.c.			
Isc PV per tracker	20Ad.c.			
Grid terminal				
Rated voltage	220/230/240 Va.c.			
Rated frequency	50/60 Hz			
Maximum continuous output current	7.5Aa.c.	10Aa.c.	15Aa.c.	16Aa.c.
Rated output current	6.8/6.5/6.3 Aa.c.	9.1/8.7/8.3 Aa.c.	13.6/13.0/12.5 Aa.c.	16/15.7/15.0 Aa.c.
Maximum output current	7.5/7.2/6.9 Aa.c.	10.0/9.6/9.2 Aa.c.	15.0/14.3/13.8 Aa.c.	16/15.7/15.0 Aa.c.
Rated output power	1500W	2000W	3000W	3600W
Rated output Apparent power	1500VA	2000VA	3000VA	3600VA
Maximum continuous output Apparent power	1650VA	2200VA	3300VA	3600VA
Power factor (Cos phi), adjustable	0.8 leading ~ 0.8 lagging			
Enclosure	IP65			
Temperature Range	-25°C ~ +60°C (derating at 45°C)			
Protective Class	I			
Altitude	up to 4000 m			



Attestation of Conformity

No. N8A 001965 0021 Rev. 02

Model	SE 4KTL-D1/G2P	SE 4.6KTL-D1/G2P	SE 5KTL-D1/G2P	SE 6KTL-D1/G2P
PV terminal				
Vmax. PV	550Vd.c.			
MPPT Voltage Range	70-540Vd.c.			
MPPT Voltage Range (full load)	140 ~ 480Vd.c.	160 ~ 480Vd.c.	170 ~ 480Vd.c.	210 ~ 480Vd.c.
MPPT Tracker number	2			
Max. continuous PV input current per tracker	15/15Ad.c.			
Isc PV per tracker	20/20Ad.c.			
Grid terminal				
Rated voltage	220/230/240 Va.c.			
Rated frequency	50/60 Hz			
Maximum continuous output current	20Aa.c.	23Aa.c.	25Aa.c.	27.3Aa.c.
Rated output current	18.2/17.4/16.7 Aa.c.	20.9/20.0/19.2 Aa.c.	22.7/21.7/20.8 Aa.c.	27.3/26.1/25.0 Aa.c.
Maximum output current	20.0/19.1/18.3 Aa.c.	23.0/22.0/21.0 Aa.c.	25.0/23.9/22.9 Aa.c.	27.3/26.1/25.0 Aa.c.
Rated output power	4000W	4600W	5000W	6000W
Rated output Apparent power	4000VA	4600VA	5000VA	6000VA
Maximum continuous output Apparent power	4400VA	5060VA	5500VA	6000VA
Power factor (Cos phi), adjustable	0.8 leading ~ 0.8 lagging			
Enclosure	IP65			
Temperature Range	-25°C ~ +60°C (derating at 45°C)			
Protective Class	I			
Altitude	up to 4000 m			



Product Service

Attestation of Conformity

No. N8A 001965 0021 Rev. 02

Model	VP 2KTL-S1/G2P	VP 3KTL-S1/G2P	VP 3.6KTL-S1/G2P
PV terminal			
Vmax. PV	500Vd.c.		
MPPT Voltage Range	50-490Vd.c.		
MPPT Voltage Range (full load)	140 ~ 430Vd.c.	210 ~ 430Vd.c.	250 ~ 430Vd.c.
MPPT Tracker number	1		
Max. continuous PV input current per tracker	15Ad.c.		
Isc PV per tracker	20Ad.c.		
Grid terminal			
Rated voltage	220/230/240 Va.c.		
Rated frequency	50/60 Hz		
Maximum continuous output current	10Aa.c.	15Aa.c.	16Aa.c.
Rated output current	9.1/8.7/8.3 Aa.c.	13.6/13.0/12.5 Aa.c.	16/15.7/15.0 Aa.c.
Maximum output current	10.0/9.6/9.2 Aa.c.	15.0/14.3/13.8 Aa.c.	16/15.7/15.0 Aa.c.
Rated output power	2000W	3000W	3600W
Rated output Apparent power	2000VA	3000VA	3600VA
Maximum continuous output Apparent power	2200VA	3300VA	3600VA
Power factor (Cos phi), adjustable	0.8 leading ~ 0.8 lagging		
Enclosure	IP65		
Temperature Range	-25°C ~ +60°C (derating at 45°C)		
Protective Class	I		
Altitude	up to 4000 m		

Tested according to:

EN 62109-1:2010
EN 62109-2:2011

Page 5 of 5

After preparation of the necessary technical documentation as well as the EU declaration of conformity the required CE marking can be affixed on the product. The declaration of conformity is issued under the sole responsibility of the manufacturer. Other relevant EU-directives have to be observed.