

## DATA LOGGER V1000+



- Built-in web server for LAN monitoring
- 12 Months of data storage
- Automatic network clock synchronization
- RS485 interface for inverter connection
- Standard RJ45 patch cable
- Power export control supported

Model	V1000+
Connection	Inverter: RS485 Router: RJ45
Access Number	40pcs
Transmission Maximum Distance	1200m
Display	LED
<b>Input</b>	
Input Voltage	Input: AC 90V-250V 50/60Hz Output: DC 5V
Static Current Consumption	1A
<b>General</b>	
Operating Temperature	-25°C~55°C
Humidity	10%~95% relative humidity, no condensation
IP Rating	IP20
Dimension (L*W*H)	118mm*78mm*29mm
<b>Certification</b>	
Safety	FCC, CE, ROHS



www.senergytec.com

Shenzhen Senergy Technology Co., Ltd.

Tel: +86-755-8524-5541 ext. 2800

Email: salesglobal@senergytec.com

Address: 11th floor, Building 6, Skyworth Innovation Valley, No. 8 Tangtou No. 1 Road, Bao'an District, Shenzhen, P.R.China

## WiFi Communication Module SE WIFI-R

- Easy plug-and-play installation for quick and convenient setup
- Preferred monitoring solution for residential use



Model	SE WIFI-R
Connection	TTL
Standards	802.11 b/g/n
Transmission Maximum Distance	100m Unobstructed environment
Setting	APP / WEB
<b>Input</b>	
Input Voltage	DC 5V
Static Power Consumption	<1.6W
<b>General</b>	
Operating Temperature	-25°C~60°C
Humidity	0%~100% relative humidity, no condensation
IP Rating	IP65
Dimension (L*W*H)	71mm*41mm*92mm
<b>Certification</b>	
Safety	FCC / CE-RED / SRRC

## LAN Communication Module SE LAN-R

- Easy plug-and-play installation for quick and convenient setup
- Mobile internet monitoring, ideal for rural and remote areas



Model	SE LAN-R
Connection	TTL
Standards	IEEE 802.3
Transmission Maximum Distance	100m CAT5
Setting	APP
<b>Input</b>	
Input Voltage	DC 5V
Static Power Consumption	<1.6W
<b>General</b>	
Operating Temperature	-25°C~60°C
Humidity	0%~100% relative humidity, no condensation
IP Rating	IP65
Dimension (L*W*H)	71mm*41mm*117mm
<b>Certification</b>	
Safety	FCC, CE-RED, SRRC