


DATA LOGGER V1000+



- Built-in web server for LAN monitoring
- 12 Months of data storage
- Automatic network clock synchronization
- RS485 interface for inverter connection
- Standard RJ45 patch cable
- Power export control supported

Model	V1000+
Connection	Inverter: RS485 Router: RJ45
Access Number	40pcs
Transmission Maximum Distance	1200m
Display	LED
Input	
Input Voltage	Input: AC 90V-250V 50/60Hz Output: DC 5V
Static Current Consumption	1A
General	
Operating Temperature	-25 C ~55 C
Humidity	10%~95% relative humidity, no condensation
IP Rating	IP20
Dimension (L*W*H)	118mm*78mm*29mm
Certification	
Safety	FCC, CE, ROHS



WIFI COMMUNICATION MODULE SE WIFI-R



- Easy plug-and-play installation for quick and convenient setup
- Preferred monitoring solution for residential use

Model	SE WIFI-R
Connection	TTL
Standards	802.11 b/g/n
Transmission Maximum Distance	100m Unobstructed environment
Setting	APP / WEB
Input	
Input Voltage	DC 5V
Static Power Consumption	<1.6W
General	
Operating Temperature	-25°C ~60°C
Humidity	0%~100% relative humidity, no condensation
IP Rating	IP65
Dimension (L*W*H)	71mm*41mm*92mm
Certification	
Safety	FCC / CE-RED / SRRC

LAN COMMUNICATION MODULE SE LAN-R



- Easy plug-and-play installation for quick and convenient setup
- Mobile internet monitoring, ideal for rural and remote areas

Model	SE LAN-R
Connection	TTL
Standards	IEEE 802.3
Transmission Maximum Distance	100m CAT5
Setting	APP
Input	
Input Voltage	DC 5V
Static Power Consumption	<1.6W
General	
Operating Temperature	-25°C ~60°C
Humidity	0%~100% relative humidity, no condensation
IP Rating	IP65
Dimension (L*W*H)	71mm*41mm*117mm
Certification	
Safety	FCC, CE-RED, SRRC

