

SINGLE PHASE & SINGLE MPPT

SE 2/3/3.6KTL-S1/G2P

Application: Residential Use



SUPERIOR PERFORMANCE

- Maximum efficiency of 97.8%
- Large string current, compatible with large PV modules
- Wide voltage range, compatible with various power grids



HIGH RELIABILITY

- IP65 protection level for outdoor installation
- Optional: DC/AC Type II SPD
- Optional: AFCI function



INTELLIGENT MAINTENANCE

- Power consumption monitoring
- Remote configuration and upgrade
- Quick commissioning via mobile app



Model	SE 2KTL-S1/G2P	SE 3KTL-S1/G2P	SE 3K6TL-S1/G2P
Efficiency			
Max. Efficiency		97.8%	
European Efficiency	96.5%	96.8%	96.8%
Input (PV)			
Max. Input Voltage		500V	
Max. PV Configuration (STC)		150%	
Rated Input Voltage		360V	
Max. Input Current		15A	
Max. Short Circuit Current		20A	
Start Input Voltage		70V	
MPPT Operating Voltage Range		50V-490V	
Max. Number of PV Strings		1	
No. of MPPTs		1	
Output (Grid)			
Rated AC Active Power	2,000W	3,000W	3,600W
Max. AC Apparent Power	2,200VA	3,300VA	3,600VA
Max. AC Output Current	10A	15A	16A
Rated AC Voltage	220V/230V/240V, L+N+PE		
AC Voltage Range ^①	160V-300V (Adjustable)		
Rated Grid Frequency	50Hz / 60Hz		
Grid Frequency Range ^②	45Hz-55Hz / 55Hz-65Hz (Adjustable)		
THDI	<3% (Rated Power)		
DC Current Injection	<0.5%In		
Power Factor	>0.99 Rated Power (Adjustable 0.8 LD - 0.8 LG)		
Protection			
DC Switch	Yes		
Anti-Islanding Protection	Yes		
AC Overcurrent Protection	Yes		
AC Short Circuit Protection	Yes		
DC Reverse Protection	Yes		
Surge Arrester	DC Type III (Type II optional) / AC Type III (Type II optional)		
Insulation Detection	Yes		
Leakage Current Protection	Yes		
General			
Topology	Transformerless		
IP Rating	IP65		
Night Self Consumption	<1W (Standard)		
Cooling	Natural Cooling		
Operating Temperature Range	-25 °C -60 °C		
Relative Humidity Range	0-100%		
Max. Operating Altitude	4000m		
Dimensions (W*H*D)	320mm*344mm*137mm		
Weight	6.5Kg		
HMI & COM			
Display	Wireless & APP+LED, LCD (Optional)		
Communication	Optional: WiFi / GPRS / RS485 / LAN		
Certification			
Safety	IEC62109-1, IEC62109-2		
Grid Code	DE-AR-N 4105, EN 50549-1, CEI 0-21, UNE 206001/206002-1, IEC 61727/62116, ORDINANCE n°140 2022, IEEE 1547, UL 1741, AS 4777, VDE 0126-1		
Warranty	5 Years		

Remarks: · ^{①②}The range of output voltage and frequency may vary depending on different grid codes.
· Specifications are subject to change without advanced notice.

