


SINGLE PHASE HYBRID INVERTER

SE 3/3.6/3.68/4.6/5/6KHB-D1/LV



Features

LCD touch screen, Easy to operate

Support smart load/generator

Support up to 9pcs in parallel

Compact and Lightweight, Convenient for transportation and installation

Large input current, Compatible with high-power solar modules

Seamless transition to backup mode, Enjoy green energy in a power outage

IP65: Indoor or outdoor installation



Model	SE 3KHB-D1/LV	SE 3K6HB-D1/LV	SE 3K68HB-D1/LV	SE 4K6HB-D1/LV	SE 5KHB-D1/LV	SE 6KHB-D1/LV
Efficiency						
Max. Efficiency (PV to AC)				98%		
Eur. Efficiency (PV to AC)				97%		
Max. Efficiency (BAT to AC)				96%		
Input (PV)						
Max. PV Input Power				10000W		
Max. PV Voltage				550V		
Start-up Voltage				90V		
MPPT Voltage Range				70V-540V		
MPPT Voltage Range @Full Load				278V-440V		
Max. Input Current				18A/18A		
Max. Short Circuit Current				25A/25A		
Nos. of MPPT				2		
String per MPPT				1/1		
Input/Output (BAT)						
Battery Type	Lithium-ion/Lead-acid					
Nominal Battery Voltage	48V					
Battery Voltage Range	40V-65V					
Max. Charging/Discharging Current	75A/75A		110A/110A		135A/135A	
Max. Charging/Discharging Power	4,000W/4,000W		5,500W/ 5,500W		6,600W/ 6,600W	
Input/Output (Grid)						
Nominal AC Output Power	3,000W	3,600W	3,680W	4,600W	5,000W	6,000W
Max. AC Apparent Power	3,300VA	3,960VA	3,680VA	4,600VA	5,500VA	6,600VA
Max. AC Output Power (PF=1)	3,300W	3,960W	3,680W	4,600W	5,500W	6,600W
Max. AC Output Current	15A	18A	16.7A	21A	25A	28.7A
Max. Input Power From Grid	9,000W					
Max. Input Current From Grid	41A					
Rated Grid Voltage	220V/230V/240V, L+N+PE					
Grid Voltage Range	150V-300V (Adjustable)					
Rated Grid Frequency	50Hz/60Hz					
AC Frequency Range	45Hz-55Hz/55Hz-65Hz (Adjustable)					
Power Factor	> 0.99 @rated power (Adjustable 0.8 LD - 0.8 LG)					
THDI	<3% (Rated Power)					
Output (Back up)						
Nominal Output Power	3,000W	3,600W	3,680W	4,600W	5,000W	6,000W
Rated AC Output Current	13.6A/13.0A/12.5A	16.7A/16.0A/15.3A	16.7A/16.0A/15.3A	20.9A/20.0A/19.2A	22.7A/21.7A/20.8A	27.3A/26.1A/25 A
Peak Output Power (Off Grid @1min)	3,600VA	4,320VA	4,416VA	5,520VA	6,000VA	7,200VA
Peak Output Power (Off Grid @10S)	6,000VA	7,200VA	7,360VA	9,200VA	10,000VA	10,000VA
Nominal Output Voltage	220V/230V/240V, L+N+PE					
Nominal Output Frequency	50Hz/60Hz					
Transfer Time	10ms (typical)					
THDV	<3% (Rated Load)					
Protection						
Protection Category	Class I					
DC Switch	Yes					
Anti-islanding Protection	Yes					
AC Over Current Protection	Yes					
AC Over Voltage Protection	Yes					
AC Short Circuit Protection	Yes					
DC Reverse Protection	Yes					
Surge Arrester	DC Type III, AC Type III (Type II Optional)					
PV Insulation Detection	Yes					
Leakage Current Protection	Yes					
General						
Max. Operation Altitude	4000m (>2000m derating)					
Protection Degree	IP65					
Operating Temperature Range	-25 C ~60 C (>45 C derating)					
Relative Humidity	0~100%					
Cooling	Natural Cooling				Smart Fan Cooling	
Mounting	Wall bracket					
Dimensions (W*H*D)	378mm*453mm*206mm					
Weight	19Kg					
HMI & COM						
Display	LED, LCD (Optional)					
Communication Interface	RS485/CAN (for BMS), RS485 (for Meter), 2*DO, 2*DI, Optional: Wi-Fi/LAN					
Certification						
Grid	IEC 61727, NRS 097-2-1, G98, G99, VDE4105, EN50549-1/-10, AS4777.2					
Safety	IEC/EN 62109-1&2					
EMC	IEC/EN 61000, EN 62920					
Warranty	5 Years/10 Years (Optional)					

Remarks: · The range of output voltage and frequency may vary depending on different grid codes.
· Specifications are subject to change without advanced notice.

