

SE 5/6KHB-D2/UL, SE 7.6/10/11.4KHB-T2/UL

Application: Residential Use



Excellent Performance

- Integrated 3 MPPTs for multiple array orientations
- Support high power module with 30A PV input current
- Max battery charge/discharge current of 210A



Safety & Reliability

- IP65: Indoor or outdoor installation
- Built-in breaker for safety and reliability
- Integrated arc fault circuit interrupter (AFCI 2.0) and rapid shutdown



High Flexibility

- Support 40-64V Lithium or Lead-acid battery
- Max. 9 units parallel for on-grid and off-grid operation
- Support smart load/generator/AC Coupling




Intelligent Maintenance

- Intelligent management, local & remote monitoring
- 3 application modes, mixed with battery scheduling



SPLIT
PHASE
& LV
BATTERY



	SE 5KHB-130-D2/UL	SE 6KHB-130-D2/UL	SE 7K6HB-180-T2/UL	SE 10KHB-210-T2/UL	SE 11K4HB-210-T2/UL
Efficiency					
Max. Efficiency (PV to AC)	98.0%				
CEC. Efficiency	96.5%				
Input (PV)					
Max. PV Usable Power	7,500W	9,000W	12,000W	15,000W	15,000W
Max. PV Voltage	600V				
Start-up Voltage	90V				
MPPT Operating Voltage Range	70V-540V				
Max. Input Current Per MPPT	30A/22A	30A/22A	30A/22A/22A	30A/22A/22A	30A/22A/22A
Max Short Current Per MPPT	40A/30A	40A/30A	40A/30A/30A	40A/30A/30A	40A/30A/30A
String Per MPPT	2/2	2/2	2/2/2	2/2/2	2/2/2
Nos. of MPPT	2	2	3	3	3
Input/Output (BAT)					
Battery Type	Lithium-ion/Lead-acid				
Nominal Battery Voltage	48V				
Battery Voltage Range	40V-64V				
Max. Charge/Discharge Current	210A/130A	210A/130A	210A/180A	210A/210A	210A/210A
Max. Charge/Discharge Power	10,000W/5,000W	10,000W/6,000W	10,000W/7,600W	10,000W/10,000W	10,000W/10,000W
Output (Grid)					
Nominal AC Output Power	5,000W	6,000W	7,600W	10,000W	10,000W
Max. AC Output Apparent Power	5,500VA	6,600VA	7,600VA	11,000VA	11,400VA
Max. AC Output Power (PF=1)	5,500W	6,600W	7,600W	11,000W	11,400W
Nominal AC Output Current	20.9A	25A	31.7A	41.7A	41.7A
Max. AC Output Current	22.9A	27.5A	31.7A	45.8A	47.5A
Nominal Grid Voltage	120V/240V (Split phase)/120V/208V (2/3 phase)				
Nominal Grid Frequency	50Hz/60Hz				
Grid Frequency Range	45Hz-55Hz/55Hz-65Hz (Adjustable)				
Power Factor	> 0.99@Rated power (Adjustable 0.8 LG - 0.8 LD)				
THDI	<3%@Rated Power				
Output (Back up)					
Nominal Output Power	5,000W	6,000W	7,600W	10,000W	10,000W
Max. AC Output Power (PF=1)	5,500W	6,600W	7,600W	11,000W	11,400W
Nominal Output Current	20.9A	25A	31.7A	41.7	41.7A
Peak Output Apparent Power(1s)	10,000VA	12,000VA	15,200VA	20,000VA	20,000VA
Nominal Output Voltage	120V/240V (Split phase)/120V/208V (2/3 phase)				
Nominal Output Frequency	50Hz/60Hz				
Transfer Time	< 10ms (Typical)				
THDV	<3%@100% R Load				
Protection					
Protection Category	Class I				
DC Switch	Yes				
Anti-islanding Protection	Yes				
AC Overcurrent Protection	Yes				
DC/AC Overvoltage Protection	DC Type II, AC Type IV				
AC Short Circuit Protection	Yes				
DC Reverse connection	Yes				
Surge Arrester	DC Type II, AC Type II				
Insulation Resistance Detection	Yes				
Leakage Current Protection	Yes				
AFCI 2.0/RSD Monitoring	Yes				
General					
Max. Operation Altitude	4,000m (>2,000m derating)				
Ingress Protection Degree	NEMA 3R				
Operating Temperature Range	-25°C~60°C (>45°C derating)				
Relative Humidity	0~100%				
Cooling Method	Smart Cooling				
Mounting	Wall bracket				
Dimensions (W*H*D)	16.5*31.5*9.4 inch (420mm*800mm*240mm)				
Weight	44kg/97lb				
HMI & COM					
Display	Wireless & APP + LED , LCD (Optional)				
Communication Interface	CAN (for BMS), RS485 (for meter), RS485, CAN (for parallel), Optional: Wi-Fi/LAN				
Certification					
Safety	UL 1741/CSA C22.2/UL 1699B				
EMC	FCC Part 15 Class B				
Grid Code	UL 1741SA, UL 1741SB, UL 1741 PCS CRD, IEEE1547, HECO SRD 2.0, CSIP				
Warranty	5 Years/10 Years (Optional)				

Remarks: · The range of output voltage and frequency may vary depending on different grid codes.
· Specifications are subject to change without advanced notice.