

SE 75KTL-Q3/G2

Application: Commercial & Industrial Sites



Superior Performance

- Maximum efficiency of 98.8%
- Large string current, compatible with large PV modules
- Maximum 150kW PV input power



High Reliability

- IP66 protection level for outdoor installation
- DC/AC Type II SPD
- Optional: AFCI 2.0, Night SVG, I/V detection, and integrated PID



Intelligent Maintenance

- Power consumption monitoring
- Remote configuration and upgrade
- Quick commissioning via mobile app
- String level current detection



THREE PHASE & MULTIPLE MPPT



SE 75KTL-Q3/G2**Efficiency**

Max. Efficiency	98.8%
European Efficiency	98.2%

Input (PV)

Max. Input Voltage	1100V
Max. PV Configuration (STC)	200%
Rated Input Voltage	620V
Max. Input Current	64A/64A/48A/48A
Max. Short Circuit Current	72A/72A/54A/54A
Start Input Voltage	250V
MPPT Operating Voltage Range	180V-1000V
Max. Number of PV Strings	4/4/3/3
No. of MPPTs	4

Output (Grid)

Rated AC Active Power	75,000W
Max. AC Apparent Power	82,500VA
Max. AC Output Current	3*125A
Rated AC Voltage	380V/400V/415V, 3W+N+PE
AC Voltage Range①	320V-480V (Adjustable)
Rated Grid Frequency	50Hz/60Hz
Grid Frequency Range②	45Hz-55Hz/55Hz-65Hz (Adjustable)
THDI	<3%@Rated Power
DC Current Injection	<0.5%@Rated Current
Power Factor	>0.99@Rated power (Adjustable 0.8 LD - 0.8 LG)

Protection

DC Switch	Yes
Anti-Islanding Protection	Yes
AC Overcurrent Protection	Yes
AC Short Circuit Protection	Yes
DC Reverse Protection	Yes
Surge Arrester	DC Level II/AC Type II
Insulation Detection	Yes
Leakage Current Protection	Yes
AFCI 2.0	Optional
PID Recovery	Optional
PV String Monitoring	Yes
Consumption Monitoring	Optional

General

Topology	Transformerless
IP Rating	IP66
Night Self Consumption	<10W (Standard)
Cooling Method	Smart Cooling
Operating Temperature Range	-25°C~60°C
Relative Humidity Range	0-100%
Max. Operating Altitude	4000m
Dimensions (W*H*D)	635mm*530mm*236mm
Weight	43.3kg

HMI & COM

Display	Wireless & APP+LED, LCD (Optional)
Communication Interface	RS485, Optional: Wi-Fi/GPRS/LAN

Certification

Safety	IEC 62109-1, IEC 62109-2
Grid Code	IEC 61727/62116, IEC 60068, IEC 61683, PORTARIA N° 140, PORTARIA N° 515
Warranty	5 Years/10 Years (Optional)

Remarks: · ①②The range of output voltage and frequency may vary depending on different grid codes.
· Specifications are subject to change without advanced notice.

